

SAFETY DEVICE FOR STRIP
DISPENSING MACHINE

INS A17

5 The invention relates to the technical field
of means of dispensing a predetermined length of
strip material wound on a reel.

10 The invention applies to machines for the
simultaneous dispensing and cutting of paper, wadding
or wipe material in all hand-wipe or toilet paper
dispensing applications.

15 The Applicant has developed many dispensing
machines of this type which are defined, in
particular, in European Patent 145 622.

20 A machine of this type comprises a housing
having a parallelepiped configuration containing a
drum rotatably mounted with respect to the lateral
end shields of the housing, this drum being
designed to internally accommodate a cutting
mechanism with a serrated blade capable of moving
out of the drum in a given cycle when the drum
rotates as a result of the strip of paper being
25 pulled by a user. A device to start and return the
drum described in the Applicant's previous patent
makes it possible to cut the strip of material
cleanly.

30 The reel of material located above the drum is
held by end shields located either side of the housing
of the machine and may or may not rest on the drum.

35 The strip of material to be dispensed passes over
the rear of the drum so that it can be dispensed through a
slit in the lower part of the housing.

09966028 092801
T08260 82099660

In order to ensure that the strip of paper or material pulled by the user is ejected from the machine along a satisfactory trajectory, the Applicant has made provision to design the drum with
5 a groove which guides and accommodates an endless transmission belt which is wound around a shaft, said shaft being secured between the lateral sides of the housing and located close to the area of the opening through which the strip of paper is ejected from the
10 bottom of the machine.

This shaft also has a groove which is located in close relationship and in the same plane as the groove on the drum so that, when the drum rotates in
15 order to obtain cutting, said belt spins the shaft and correctly guides the strip of paper towards the outlet of the machine.

The arrangements of this type are described in
20 the above-mentioned European Patent.

Although these arrangements ensure satisfactory operation of the paper strip dispensing machine, there are still nevertheless several drawbacks resulting from
25 the way in which the strip of paper is fed and pulled through the outlet of the dispensing machine by the user.

In fact, the user often tends to pull the strip of paper to the right or left-hand side at a slant and
30 this has the effect of causing the belt to escape from the above-mentioned grooves, thus impeding operation of the machine and sometimes jamming it if the paper tears.

Very often the belt even tends to jump out of
35 the groove and this obviously has an adverse effect on the correct operation of the dispensing machine.

09966028-092801

The first solution tried to solve these drawbacks was to increase the tension of the belt in order to prevent it escaping from the groove by keeping it very tight. This first solution had a secondary disadvantage. It was apparent that it became hard to rotate the mechanism for starting the drum and difficulties were encountered in pulling the paper and strip of material in general, especially when the user's hands were wet.

10

Increasing the tension of the belt was therefore unsatisfactory and made it impossible to use the dispensing machine.

15

Another approach was to increase the diameter of the edges of the groove on the shaft so as to produce a kind of deep channel intended to prevent the part of the belt in question from escaping if the paper was pulled sideways.

20

This solution was not entirely satisfactory because, in practice, it became apparent that the middle of the paper was marked and very often split in two pieces either side of the central area when it was cut.

25

The approach adopted by the Applicant was therefore to attempt to modify the drum/safety shaft connection so as to give a satisfactory solution to the problems encountered, associated with the user pulling the strip of paper emerging from the machine sideways, exerting a greater or lesser tensile force, so as to prevent the belt escaping from its groove.

30

According to a first aspect of the invention, the control and security device allowing ejection of

35

B1 20/04/01
n2/01/01

the strip of material from a strip dispensing machine comprising a drum and a safety shaft which shuts off the lower opening through which the strip of material passes as it leaves the housing and the drum, said drum and said shaft being linked by a means of transmission consisting of a belt, is characterised in that said transmission means is float mounted between the drum and the shaft, with the central part of the shaft that accommodates said belt and faces the groove on the drum being designed with a dolly axle configuration having a dimension that exceeds the width of the groove on the drum so as to allow sideways, slanting deflection of the belt over a limited amplitude, thus tracking the direction in which the strip of paper is pulled longitudinally out of the dispensing machine by the user.

These aspects and others will become apparent from the following description.

The object of the present invention is described, merely by way of example, in the accompanying drawings in which:

- Figure 1 is a side view of a machine for dispensing strips of material designed in accordance with the invention;
- Figure 2 is a plan cross-sectional view along line 2-2 in Figure 1;
- Figure 3 is a large-scale view of the shaft designed in accordance with the invention showing the position of the belt as a function of different frontal or lateral tensile forces.

5

10

15

20

25

30

35

The strip of material wound on the reel is mounted between the upper end shields (8) so that said reel advantageously rests against the drum.

100

10

sha
bel
whi
str
sec
mach

3 This control and safety device shaft (9) is capable of accommodating belt (10) which constitutes the means which, firstly, prevents the unwanted strips of paper between the drum and secondly, forces the strip of paper into the machine's lower opening.

15 Drum (4) thus has a groove (4b) in its middle part capable of accommodating belt (10) by forming a path over which it slides.

The invention lies in the fact that the middle
20 part of the shaft (9) facing groove (4b) on drum (4)
has a dolly axle configuration (9a) of reduced
thickness (D1) compared with the cross section (D2)
of shaft (9) to accommodate belt (10).

25 The length (L1) of this dolly axle
configuration is such that it substantially exceeds
the width (L2) of the groove on the drum so that it
allows, when the strip of paper is pulled by the
user, lateral movement of amplitude α and limits the
30 lateral displacement of the belt which therefore is
subjected to significant deformation when the strip
of paper is pulled in a lateral plane.

Said belt (10) is tensioned so that it is
35 float mounted between drum (4) and safety shaft (9)

In order to ensure lateral deflection depending on the way in which the strip of paper is pulled.

Advantageously, the dolly axle (9a) shape of the above-mentioned part of the shaft is laterally locked by the walls (9b) of the shaft (9) thus forming a shoulder and limit stop so that said belt cannot escape from its groove. The float-mounted belt nevertheless remains held in its extreme position against one of the inside walls of the shaft, it does not jump out and does not move onto the outer periphery (9c) of the latter.

This float mounting and limited deflection amplitude of the transmission belt between the drum and the safety shaft makes it possible to use the dispensing machine in any situations where the strip of material is pulled sideways without the machine thereby being jammed.

20 *ins B2* In addition and incidentally, the groove (4a) on the drum may have, in the location of the slit formed in the drum, a slight extra thickness (4b) to ensure control of the position of the transmission belt during extreme deflection of the float-mounted belt along the dolly axle shape of the safety shaft.

30 *ins B3* The invention is applicable to all types of machines for dispensing strips of material which include connection by means of belt-type transmission between the drum that accommodates a cutting device and a safety shaft located in the lower part of the housing which ensures guided ejection of the strip of material.

09966028-092801

Ins C47

Without going beyond the scope of the invention, it is also feasible to double the number of means of transmission that implement the invention. In this case, the drum is designed with a

5 number of grooves which corresponds to the number of transmission belts, and facing them, the safety shaft has an identical number of dolly-axle shapes to ensure the desired operation.

10 The advantages of the invention are readily apparent.

The simplicity with which this enhancement can be implemented and the fact that it does not increase

15 the cost of manufacturing the dispensing machine and its high reliability are emphasised.

20

25

30

35

0966028-092801